



PENTA UP-CUT VARIABLE ANGLE MITER SAW

Single Head Variable Angle Up-Cut Miter Saw with digital angle display and 20" (500 mm) diameter carbide tipped saw blade.



BASE MACHINE

- Two-hand safety operator controls
- Miter angle range from -20° to 20° degrees
- Detents at common angle points of; 45° / 90° / 135°
- Digital angle read-out display
- Full cut-area safety hood with viewing window
- 20"(500 mm) carbide triple chip saw blade
- Pneumatic vertical clamps
- Hydro - pneumatic blade feed system w/ external adjustment control
- 4 HP motor - 1.25" (30mm) shaft arbor motor, 3400 maximum RPM at 60 HZ.
- Pneumatic brake for intermediate angle positions
- Spray mist system for aluminum cutting
- Ball bearing miter table for ease of angle setting
- Regulator / filter
- Blade wrenches
- Compressed air blow-off gun

TECHNICAL SPECIFICATIONS

- Power: 480V (3 Phase)
- Air: 80-100 PSI
- Weight: 770 Lbs
- Dimensions: 32.5"L x 40.5"W x 57"H
- Warranty: One year Parts

MACHINE OPTIONS

- Cut line laser
- Trimming fence
- Single phase motor
- TCT saw blade 20 5/8" (525 mm)
- TCT saw blade 20 7/8" (530 mm)
- TCT saw blade 21 5/8" (550 mm)
- Horizontal clamp

